

# SAFETY DATA SHEET

**Report No.:** CMC241022014M01

**Name of sample:** Lithium ion Battery

**Model:** CEL 503245

**Type:** 3.7V 670mAh 2.479Wh

**Client:** Dongguan Golden CEL Battery Co., Ltd.

**Address:** No.11, Yinhu Industrial park, JiaoYiTangManagement Zone, TangXia, DongGuan, GuangDong, P.R. China

**Written:** *Meiko Ma* **Approved:** *Dong Le*

**Reviewed:** *Dylan Dou*

**Date of issue:** 2025.01.02 **Seal of CMC**



## CMC Testing International (Shenzhen) Co., Ltd.

The supplier identified below generated this SDS using the CMC SDS template. CMC did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. CMC makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS.

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

## Safety Data Sheet

### Section 1- Identification of the Substance/Preparation and of the Company/Undertaking

#### (a) Product identifier

Name of Sample	Lithium ion Battery	Weight	13.9g
		Size (L×W×T)	(45.3×31.9×4.4)mm
Model	CEL 503245		

#### (b) Other means of identification

**Synonyms:** None

#### (c) Recommended use of the chemical and restrictions on use

**Recommended use:** LITHIUM ION BATTERIES

**Restriction on use:** No information available.

#### (d) Details of the supplier of the product

Manufacturer	Dongguan Golden CEL Battery Co., Ltd.
Manufacturer's Address	No.11, Yinhu Industrial park, JiaoYiTangManagement Zone, TangXia, DongGuan, GuangDong, P.R. China
Contact Person	Mr. Zhi
E-mail	zhirongjian@celbattery.com
Telephone:	+86-769-82195308-8016
Fax:	+86-769-87982226
(e) Emergency phone number	+86-769-82195308-8016

### Section 2- Hazards Identification

#### (a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 3
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Specific target organ toxicity (repeated exposure)	Category 1
Carcinogenicity	Category 2
Skin sensitization	Category 1

**(b) GHS Label elements, including precautionary statements**
**Emergency Overview**
**Signal word:** Danger

**Hazard Statements**

Harmful if swallowed

Causes severe skin burns and eye damage

May cause an allergic skin reaction

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

<b>Appearance</b>	Gold	<b>Physical State</b>	Solid	<b>Odor</b>	Odorless
-------------------	------	-----------------------	-------	-------------	----------

**Precautionary Statements-  
Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves

**Precautionary Statements-  
Response**

IF EXPOSED OR CONNECTED: Get medical advice/attention. Specific treatment (see supplemental first aid/instruction on this label).  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.  
 IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and water before reuse, if skin irritation or rash occurs: get medical advice/attention if feel unwell.  
 IF INHALATION: If breathing is difficult, remove victim to fresh air and

	keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor/physician. IF SWALLOWED: Rinse mouth, do not induce vomiting, call a poison center or doctor/physician if feel unwell.
<b>Precautionary Statements-Storage</b>	Store locked up
<b>Precautionary Statements-Disposal</b>	Dispose of contents/container to an approved waste disposal plant
<b>(c) Hazards not otherwise classified (HNOC)</b>	Not applicable
<b>(d) Unknown Toxicity</b>	
<b>(e) Other information</b>	Very toxic to aquatic life with long lasting effects; Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
<b>(f) Interactions with Other Chemicals</b>	No information available.

## Section 3- Composition/Information on Ingredients

Chemical Name	CAS Number	Weight-%	Trade Secret
Lithium Cobalt Oxide (LiCoO <sub>2</sub> )	12190-79-3	37.47	*
Graphite	7782-42-5	15.35	*
Copper	7440-50-8	10.36	*
Aluminum foil	7429-90-5	9.25	*
Polypropylene	9003-07-0	1.54	*
1,1-Difluoroethylene polymer	24937-79-9	1.52	*
Polyethylene	9002-88-4	3.15	*
Styrene-Butadiene polymer	9003-55-8	0.86	*
Carboxymethyl cellulose	9000-11-7	0.74	*
Nickel	7440-02-0	1.34	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	17.49	*
Nylon	24937-16-4	0.93	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

#### Section 4- First Aid Measures

##### (a) Description of first aid measures

General Advice	First aid is upon rupture of sealed battery.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is required. May cause an allergic skin reaction. Remove and isolate contaminated clothing and shoes.
Inhalation:	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method, if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.
Ingestion:	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
Self-protection of the first aider:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

##### (b) Most important symptoms/effects, acute and delayed

Most important symptoms and effects:	Itching. Coughing and/ or wheezing. Burning sensation.
--------------------------------------	--

##### (c) Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. May cause sensitization of susceptible persons.
--------------------	--

#### Section 5- Fire Fighting Measures

##### (a) Extinguishing media

Suitable extinguishing media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media:	CAUTION: Use of water spray when fighting fire may be inefficient.

##### (b) Special hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.	
--	--



Hazardous Combustion Products	Carbon oxides.	
Explosion Data	Sensitivity to Mechanical Impact:	No.
	Sensitivity to Static Discharge:	No.

**(c) Special protective equipment and precautions for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Section 6- Accidental Release Measures**
**(a) Personal precautions, protective equipment and emergency procedures**

Personal Precautions:	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other Information:	Refer to protective measures listed in Sections 7 and 8.

**(b) Environmental Precautions**

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

**(c) Methods and materials for containment and cleaning up**

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

**Section 7- Handling and Storage**
**(a) Precautions for safe handling**

Handling:	Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.
-----------	--

**(b) Conditions for safe storage, including any incompatibilities**

Storage:	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.
Incompatible Products:	Acids. Bases. Oxidizing agent.

**Section 8 - Exposure Controls/Personal Protection**
**(a) Control parameters**

<b>Exposure Guidelines</b>			
<b>Exposure Guidelines</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>NIOSH IDLH</b>

Lithium Cobalt Oxide (LiCoO <sub>2</sub> ) 12190-79-3	TWA: 0.02 mg/m <sup>3</sup>	-	-
Graphite 7782-42-5	TWA: 1mg/m <sup>3</sup> respirable fraction all forms except graphite fibers	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> respirable fraction Synthetic (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5mg/m <sup>3</sup> F	TWA: 2.5mg/m <sup>3</sup> F TWA: 2.5mg/m <sup>3</sup> dust (vacated) TWA: 2.5mg/m <sup>3</sup>	
Copper 7440-50-8	TWA: 0.2mg/m <sup>3</sup> fume TWA: 1mg/m <sup>3</sup> Cu dust and mist	TWA: 0.1mg/m <sup>3</sup> fume TWA: 1mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100mg/m <sup>3</sup> dust, fume and mist TWA: 1mg/m <sup>3</sup> dust and mist TWA: 0.1mg/m <sup>3</sup> fume
Aluminum foil 7429-90-5	TWA: 1mg/m <sup>3</sup> respirable fraction	TWA: 15mg/m <sup>3</sup> total dust TWA: 5mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15mg/m <sup>3</sup> total dust (vacated) TWA: 5mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5mg/m <sup>3</sup> AL Aluminum	TWA: 10mg/m <sup>3</sup> total dust TWA: 5mg/m <sup>3</sup> respirable dust
Nickel 7440-02-0	TWA: 1.5mg/m <sup>3</sup>	TWA: 1mg/m <sup>3</sup> (vacated) TWA: 1 mg/m <sup>3</sup>	IDLH: 10mg/m <sup>3</sup> TWA: 0.015mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters
---------------------------	--

**(b) Appropriate engineering controls**

Engineering Measures	Showers Eyewash stations Ventilation systems
----------------------	--

**(c) Individual protection measures, such as personal protective equipment.**

Eye/Face Protection:	None required for consumer use. If there is a Hazard of contact: Tight sealing safety goggles. Face protection shield.
Skin and Body Protection:	None required for consumer use. If there is a Hazard of contact: Wear protective gloves and protective clothing.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. No information available.
------------------	--

## Section 9- Physical and Chemical Properties

### (a) Physical State

Physical state:	Solid		
Appearance:	Gold cuboid	Odor:	Odorless
Color:	Gold	Odor Threshold:	No information available

### (b) Chemical Properties

Property	Values	Remarks/ Method
pH	No data available	None known
Melting point/freezing point	No data available	None known
Initial Boiling Point And Boiling Range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (Solid, Gas)	No data available	None known
Upper/Lower Flammability Or Explosive Limits	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Relative Density	No data available	None known
Solubility(ies)	Insoluble in water	None known
Partition Coefficient: N-Octanol/Water	No data available	None known
Auto-Ignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

### (c) Other Information

Softening Point	No data available
-----------------	-------------------



VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	No data available

#### Section 10 – Stability and Reactivity

<b>(a) Reactivity</b>	No data available.
<b>(b) Chemical stability</b>	Stable under recommended storage conditions.
<b>(c) Possibility of hazardous reactions</b>	None under normal processing.
<b>(d) Hazardous polymerization</b>	Hazardous polymerization does not occur.
<b>(e) Conditions to avoid</b>	None known based on information supplied.
<b>(f) Hazardous decomposition products</b>	Carbon oxides.

#### Section 11 – Toxicological Information

##### (a) Information on the likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May be absorbed through the skin in harmful amounts. Harmful in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

##### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg ( Rat )	-	-
Nickel 7440-02-0	>9000 mg/kg ( Rat )	-	-

##### (b) Information on toxicological effects

Symptoms	Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives.
----------	---

**(c) Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Sensitization:	May cause sensitization of susceptible persons. May cause sensitization by skin contact.			
Mutagenic Effects:	No information available.			
<b>Carcinogenicity:</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.			
Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (LiCoO <sub>2</sub> ) 12190-79-3	A3	Group 2B		X
Nickel 7440-02-0		Group 2B	Reasonably Anticipated	X

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**NTP (National Toxicology Program)**

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular System (CVS). Kidney. Liver. Lungs. Heart.
Aspiration Hazard	No information available.

**(d) Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document	ATEmix (oral):	
	ATEmix (dermal):	

## Section 12-Ecological Information

**(a) Ecotoxicity**

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales romelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: =0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L
Nickel 7440-02-0	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: = 1.3 mg/L (Cyprinus carpio) 96h LC50: = 10.4 mg/L (Cyprinus carpio)		48h EC50: > 100 mg/L 48h EC50: = 1 mg/L
<b>(b) Persistence and Degradability</b>	No information available.			
<b>(c) Bioaccumulation</b>	No information available			
<b>(d) Other adverse effects</b>	No information available.			

## Section 13 – Disposal Considerations

**(a) Waste treatment methods**

Disposal methods:	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated Packaging:	Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Nickel 7440-02-0	(hazardous constituent - no waste number)	Included in waste streams: F006, F039		

**California Hazardous Waste Codes 141**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Lithium Cobalt Oxide (LiCoO <sub>2</sub> ) 12190-79-3	Toxic
Copper 7440-50-8	Toxic
Aluminum foil 7429-90-5	Ignitable powder
Nickel 7440-02-0	Toxic powder Ignitable powder

**Section 14 – Transport Information**

UN number	UN3480 Lithium ion batteries (including lithium ion polymer batteries) (limited to a maximum of 30% SoC).		
Hazard Class:	Class 9	Packing grade:	/
UN number	UN3481 Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion polymer batteries).		
Hazard Class:	/	Packing grade:	/
Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises.			
ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IB, PI 966 Section II and PI 967 Section II appropriate of IATA DGR 66th (2025 Edition) for transportation.		
IMDG CODE:	The batteries are not restricted to IMDG Code 2022 Edition (Amdt 41-22) according to special provision 188.		
UN number	UN3480 Lithium ion batteries (including lithium ion polymer batteries). UN3481 Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion polymer		

	batteries).		
Hazard Class:	/	Packing grade:	/
EmS No.	F-A S-I		
ADR/ ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2023.		
In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria. The batteries should be well protected against short circuits.			

## Section 15 – Regulatory Information

### (a) International Inventories

TSCA:	Complies.
DSL:	All components are listed either on the DSL or NDSL.
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List	

### (b) US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 – Threshold Values %
Lithium Cobalt Oxide (LiCoO <sub>2</sub> )	12190-79-3	37.47	0.1
Copper	7440-50-8	10.36	1.0
Aluminum foil	7429-90-5	9.25	1.0
Nickel	7440-02-0	1.34	0.1

#### SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40



CFR 122.42)				
Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	
Nickel 7440-02-0		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Aluminum foil 7429-90-5			
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

**(c) US State Regulations**
**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Nickel - 7440-02-0	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (LiCoO <sub>2</sub> ) 12190-79-3	X		X	X	X
Graphite 7782-42-5	X	X	X		
Copper 7440-50-8	X	X	X	X	X
Aluminum foil 7429-90-5		X		X	
Nickel 7440-02-0	X	X	X	X	X

**(d) International Regulations**

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Graphite 7782-42-5		Mexico: TWA= 2 mg/m <sup>3</sup>



CMC TESTING  
众检 检验

Report No.: CMC241022014M01

Copper 7440-50-8		Mexico: TWA= 1 mg/m3 Mexico: TWA= 0.2 mg/m3 Mexico: STEL= 2 mg/m3
Aluminum foil 7429-90-5		Mexico: TWA 10 mg/m3
Nickel 7440-02-0		Mexico: TWA= 1 mg/m3

Mexico - Occupational Exposure Limits - Carcinogens



Canada
WHMIS Hazard Class
Non-controlled

## Section 16 – Additional Information

<b>NFPA</b>	<b>Health Hazards</b>	1	<b>Flammability</b>	0	<b>Instability</b>	0	<b>Physical and Chemical Hazards</b>	-
<b>HMIS</b>	<b>Health Hazards</b>	0	<b>Flammability</b>	0	<b>Physical Hazard</b>	0	<b>Personal Protection</b>	X

Revision Note: No information available

Sample photo:


**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

\*\*\*\*\***End of report**\*\*\*\*\*

Testing laboratory: CMC Testing International (Shenzhen) Co., Ltd.

Address: 1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: 400-1668-320 E-mail: [info@cmczj-lab.com](mailto:info@cmczj-lab.com) <http://www.cmczj-lab.com>

16 / 16