MSDS

MATERIAL SAFETY DATA SHEET

- Prepared For : Earfun Technology (HK) Limited FLAT/RM A 9F, SILVERCORP INTERNATIONAL TOWER 707-713 NATHAN ROAD MONGKOK KL, HONGKONG
- Prepared By : Shenzhen LCS Compliance Testing Laboratory Ltd. Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Issue Date : 2021.03.31

Report Number : LCS210304080ASD



Approved by:

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD.

REPORT NO .: LCS210304080ASD

* The MSDS is prepared based on the information provided by client. The contents and formats of this MSDS are revised as per client's request.

client's request.					
Section	1-Chen	nical Produc	t and Company Ide	entification	
Product Name	Charging Case				
Model	TW101				
Trade Mark	N/A				
Potingo	Battery: 3.7V, 400mAh, 1.48Wh				
Ratings	Output: 5.0V				
Weight	36.8g				
Manufacturer	Chongqing VDL Electronics Co., Ltd.				
Manufacturer	Building 1-4, Puli Industrial New Area, Zhaojia Street, Kaizhou District, Chongqing, C				
address	hina				
Emergency Telephone	+86-755-29961201				
Fax	+86-23-5297 59699				
	Secti	on 2- Compo	osition Information	1	
Chemical Composition		CAS No.	Weight (%)	Trade Secret	
Lithium cobaltate	12190-79-3		15 - 40	*	
Graphite	7782-42-5		10 - 30	*	
Phosphate(1-), hexafluoro-, lithium	21324-40-3		10 - 30	*	
Copper	7440-50-8		7-13	*	
Aluminium	7429-90-5		5-10	*	
Nickel	7440-02-0		1-5	*	
" * " The exact	percentage	(concentration) of c	composition has been withheld	d as a trade secret.	
	Sec	tion 3- Haza	rds Identification		
Emergency overview:		N/A			
Classification according to GHS		Not a dangerous substance according to GHS			
Label elements:					
Hazard pictogram(s)		Not Applicable			
Signal word	Signal word		Not Applicable		

REPORT NO.: LCS210304080ASD

	KEI OKT NO.: 200210304000A3D	
Hazard statement(s)	Not Applicable	
Precautionary statement(s):		
Prevention	Not Applicable	
Response	Not Applicable	
Disposal	Not Applicable	
Environmental hazards:	No relevant information	
Important symptoms:	See section 11 for more information	
S	ection 4- First Aid Measures	
Eye contact	Flush eyes with plenty of water for least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.	
Skin contact	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.	
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.	
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.	
Sec	tion 5- Fire Fighting Measures	
Flash Point	N/A	
Auto-Ignition Temperature	N/A	
Extinguishing Media	H ₂ O, CO ₂	
Special Fire-Fighting Procedures	Self-contained breathing apparatus	
Unusual Fire and Explosion Hazards	Cell may vent when subjected to excessive heat-exposing battery contents	
Hazardous Combustion Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.	
Ocation	C. Assidental Delessa Massures	

Section 6- Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime.

Environment precautions:

Do not allow product to reach sewage system or any water source.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

REPORT NO.: LCS210304080ASD

Methods and material for containment and cleaning up:

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

Section 7- Handling and Storage				
The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.				
Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.				
The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.				
Section 8- Exposure Controls/Personal Protection				
Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.				
Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear suitable protective clothing and gloves if handling an open or leaking battery. Hand protection: Wear suitable gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.				
Have a safety shower and eye wash fountain readily available in the immediate work area.				
Do not eat, drink, or smoke in work area. Maintain good housekeeping.				
Section 9- Physical and Chemical Properties				
Solid				
Black				
Not Applicable				
Not Applicable				

Not Applicable

Melting point/freezing point

REPORT NO.: LCS210304080ASD

	REPORT NO.: LCS210304080ASD			
Boiling Point and Boiling range	Not Applicable			
Flash Point	Not Applicable			
Upper/lower flammability or explosive limits	Not Applicable			
Vapor Pressure	Not Applicable			
Vapor Density	Not Applicable			
Relative density	Not Applicable			
Solubility in Water	Not Applicable			
Auto-ignition temperature	Not Applicable			
Decomposition temperature	Not Applicable			
Evaporation rate	Not Applicable			
Flammability (soil, gas)	Not Applicable			
Viscosity	Not Applicable			
Section 10- Stability and reactivity				
Stability	The product is stable under conditions described Section 7			
Conditions to Avoid	Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions.			
Incompatible Materials	Oxidizing agents, acid, base.			
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.			
Possibility of Hazardous Reaction	Not Applicable			
Section 11 – Toxicological Information				
Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.			
Sensitization	Not Applicable			
Neurological Effects	Not Applicable			
Teratogenicity	Not Applicable			
Reproductive Toxicity	Not Applicable			

Not Applicable

Mutagenicity (Genetic Effects)

REPORT NO.: LCS210304080ASD

Toxicologically Synergistic Materials	Not Applicable			
Section 12- Ecological Information				
Ecological Toxicity	Not Applicable			
Mobility in soil	Not Applicable			
Persistence and Degradability	Not Applicable			
Bioaccumulation potential	Not Applicable			
Other Adverse Effects	Not Applicable			
Section 13- Disposal Considerations				
Product disposal recommendation	Observe local, state and federal laws and regulations.			
Uncleaned packaging recommendation	Disposal must be made according to official regulations			
Section 14 – Transport Information				
Label for conveyance	Lithium Battery Label			
UN Number	UN 3480			
Transport hazard class(es)	9			
Packing group				
Marine pollutant	No			
UN Proper shipping name	Lithium ion Batteries (Including lithium ion polymer batteries)			
ICAO/IATA	Can be shipped by air in accordance with international Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA) DGR 62 nd Packing Instructions Section IB~II of 965 appropriately.			
IMDG CODE	International Maritime Dangerous Goods Code under Special Provision 188 IMDG CODE (Amdt.39-18)			
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road under Special Provision 188			
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail under Special Provision 188			
The dangerous goods regulations re the UN Manual of Tests and Criteria	equire that each battery design be subject to tests contained in Section 38.3 of prior to being offered for transport.			

REPORT NO.: LCS210304080ASD

Section 15- Regulatory information

Law information

《Dangerous Goods Regulations》

«Recommendation on the Transport of Dangerous Goods Model Regulations»

《International Maritime Dangerous Goods》

«Technical Instructions for the Safe Transport of Dangerous Goods»

«Classification and code of dangerous Goods»

«Consumer Product Safety Act» (CPSA)

《Federal Environmental Pollution Control Act》 (FEPCA)

《Resource Conservation and Recovery Act》 (RCRA)

《European Agreement concerning the International Carriage of Dangerous》

«Regulations concerning the International Carriage of Dangerous»

In according with all Federal, State and local laws.

Section 16- Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, concorde makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

-- End of Report --